

Data Sheet




ICE Components, Inc.
Tel 678-560-9172 Fax 678-560-9304
cust.serv@icecomp.com

www.icecomponents.com
1165 Allgood Rd., Ste. #20, Marietta, GA 30062

General Information

Customer	
Part Number	IN07151
Revision	0
Description	Inductor
Date	AUG-07-2009
Reference	--
Doc Control #	--
Issue(For ICE use only)	--

Mechanical Drawing




Specification


Item	Pins	Spec	Test Condition
Inductance @0Adc	S - F	150 nH +/- 10%	100 kHz, 1Vrms, series
Inductance @Isat at 25degC	S - F	102 nH min	100 kHz, 1Vrms, series (70 Adc)
DCR	S - F	0.29 mOhm +/- 10%	+25 deg C
Isat at 25degC	S - F	70 Adc max	
Isat at +125degC	S - F	58 Adc max	
Idc	S - F	45 Adc max	

Sample Test Data

Schematic



Recommended PCB Layout



Remark

- Isat is the current at which the inductance drops by 20%.
- Idc is the current at which the temperature of the part increases by 50 deg C.
- The nominal DCR is measured from point (a) to point (b), as shown on the mechanical drawing.
- This is RoHS compliant product.
- The max operating temperature is 130degC (ambient + temperature rise).
- Inductance vs. Current Curve and Temperature vs. Current Curve as attached.


Sample approval is required before release to production. Sample specifications take precedence over customer specifications.

Customer Signature

Rev.	Description	PRD	CHK	APP	Date	NTFY
0	Initial release	Emily	Gary	L. L. Chou	2009/8/7	2009/8/7

P/N:IN07151

Inductance vs. Current



Temperature VS Current

