

Data Sheet



Helping Engineer the Technology of Power

ICE Components, Inc.


Tel 678-560-9172 Fax 678-560-9304

cust.serv@icecomp.com

www.icecomponents.com

1165 Allgood Rd., Ste. #20, Marietta, GA 30062

Mechanical Drawing



unit:mm

General Information


Customer	
Part Number	IN11013
Revision	0
Description	Inductor
Date	MAY-03-2011
Reference	--
Doc Control #	--
Issue (For ICE use only)	--

Specification


Sample Test Data

Item	Pins	Spec	Test Condition	
Inductance @0Adc	S - F	250 nH +/- 12%	100 kHz, 1Vrms, series	
Inductance @Isat at 25degC	S - F	190 nH min	100 kHz, 1Vrms, series (78Adc)	
DCR	S - F	0.25 mOhms +/- 10%	+25 deg C	
Isat at 25degC	S - F	78 Adc max		
Isat +100degC	S - F	68 Adc max		
Isat +125degC	S - F	62 Adc max		

Schematic



Recommended PCB Layout



unit:mm

Remark

1. Isat is the current at which the inductance drops by 15% typ.
2. This is RoHS compliant product.
3. Operating temperature is 130degC max (Ambient + temperature rise).
4. Inductance vs. DC current is attached.
5. The nominal DCR is measured from point (a) to point (b), as shown on the mechanical drawing.

Sample approval is required before release to production. Sample specifications take precedence over customer specifications.

Customer Signature

Rev.	Description	PRD	CHK	APP	Date	NTFY
0	Initial release	Emily	Gary	L. L. Chou	2011/5/3	2011/5/3

P/N: IN11013

Inductance vs. Current

